

UTM[®] Universal Tank Monitor



The Universal Tank Monitor (Anova UTM[®]) is an advanced and affordable, multi-input, intrinsically safe monitor that supports a wide variety of applications. With easy installation, clip-in cables, and the ability to monitor more than one tank or input, the UTM helps drive better distribution profitability and customer service.



● Works Universally.

Universal SIM card connects to all major carriers: US Cellular, AT&T, Verizon, T-Mobile, Sprint, & their partners.

● Easy and Affordable.

Magnetic or 3M[™] Dual Lock[™] mounts, with easy installation verification via mobile app. Great pricing with financing options available.

● 20-Year Battery Life.

Long-life battery and the ability to monitor multiple tanks or a combination of measures on a single tank. Multiple inputs support a range of sensors such as tank level, pressure, meters, and others. Backed by a five year warranty.



APPLICATIONS		
TANK LEVEL		
LINE PRESSURE		
OPEN / CLOSED		



Jim Schwartzfisher
Telemetry Unit Manager

616.644.2766 • 800.537.7518 ext. 1202
jim.schwartzfisher@bergquistinc.com

Your questions answered by the people who know propane equipment.

Tank Level Sensor Options

R3D® GEN 3



R3D® GEN 4



The Rochester Dial sensor is a magnetically driven dial, that is mounted onto Rochester Junior or Senior gauges. Rochester R3D® is compatible with Gen 3 and Gen 4 Rochester Remote Ready Dials. Gen 3 and Gen 4 Rochester Remote Ready Dials also offer two versions of sensor cables - Right Angle or Straight - that are compatible with both devices.



Retail
Tanks



The Anova 645 Sensor and Dial combination is compatible with Rochester and Taylor float gauges. It comes with the universal clip adapter for junior, screw-down, and 4-bolt gauge configurations. Additional adapters are available for snap-on and senior gauges

Storage
Tanks



The Large Dial sensor is a magnetically-driven and mounted onto Rochester 4" and 8" Magnetel gauges.

Submersible
Pressure Sensor



Provides reliable submersible pressure measurements relative to atmosphere. Compatible with level sensing for a broad range of liquids (chemicals, oils, lubricants & fuels) and available in four pressure ranges: 0.3, 0.5, 1.0 or 1.5 bar - tank sizes from 1 meter to 16 meters in height.

Non-Contact Sensors



The non-contact sensor is broadly compatible across wide range of fuels, lubricants and chemicals. Taking advantage of technology advances, the Anova UTM non-contact sensor expands compatibility across liquids and significantly lowers cost of tank monitoring from traditional Submersible Differential Pressure sensors.

Features & Benefits



UNIVERSAL

- Universal SIM supports multiple cellular networks (LTE CAT-M1)
- Two inputs supporting a range of sensors including tank level, pressure, meters, and others



DEPENDABILITY

- 20-year battery life
- 5-year warranty
- Rugged, sealed, with all-weather, robust construction
- Intrinsically safe and C1D1 compliant



EASY INSTALLATION

- Magnetic mount or 3M™ Dual Lock™ Velcro
- Clip-in Rochester remote-ready cable
- On-site verification with mobile app



INTEGRATION

- Seamless integration with supply-chain ERP software



REPORTING

- Half-hourly data sampling and configurable alarms, with daily reporting



INDUSTRY EXPERTISE

Bergquist dedicated technical support and training staff



Jim Schwartzfisher

616.644.2766

800.537.7518 ext.1202

jim.schwartzfisher@bergquistinc.com

How It Works



High-reliability sensors regularly check asset conditions



Measurements and alerts are communicated to secure cloud platform



View readings, build forecasts, and create reports



Schedule efficient deliveries and respond quickly to customer needs