





CZ 457

INSTALLATION INSTRUCTIONS



Thank you for purchasing this Timney Trigger. It has been designed and manufactured to provide you with a lifetime of dependable service. Each trigger is hand tested and calibrated on a rifle action before leaving our factory. Please read these instructions fully before you begin installing the trigger, you'll be glad you did.

TOOLS NEEDED:



T-20 Torx screwdriver



5/64" Hex Wrench

TIMNEY TRIGGER GUARANTEE

Every possible care has been taken in the design and construction of this trigger. If any issues arise with your Timney trigger under conditions of normal use and service, necessary repairs, including parts and labor, will be made at no added charge to the purchaser, providing our inspection reveals parts were not damaged through accident, misuse, abuse, or other causes beyond our control. We neither assume nor imply any oral or statutory warranties, and we neither assume nor authorize any person to assume us for any obligation or liability in connection with this trigger. Repairs or disassembly of this trigger in any manner without specific authorization voids this guarantee.

LEGAL DISCLAIMER

Failure to comply with our installation instructions and improper installation of this trigger can result in severe bodily harm or death. Only install this trigger on the make and model of the firearm specified. Always ensure your firearm is unloaded and safe before installing this trigger. By purchasing this product, you agree to our disclaimer. Visit www.timneytriggers.com/disclaimer to read the full disclaimer.

IF YOU HAVE TROUBLE CHECK OUT TROUBLESHOOTING STEPS ON WWW.TIMNEYTRIGGERS.COM OR CONTACT US

Need help with your install? Contact our customer service team via phone or email or assistance.
Phone: 623-223-1111 Support: technicalsupport@timneyusa.com

INSTALLATION INSTRUCTIONS

- 1** Before beginning work on any firearm, remove the ammunition source and double check to ensure the chamber is empty.
- 2** Remove the bolt
- 3** Remove the action from the stock or chassis by removing the two action screws in the bottom metal.
- 4** Remove the Torx screw holding the stock trigger in place and remove the cross pin in the back of the trigger pack.
- 5** Drop in the new Timney trigger pack, insert the cross pin and re-install the Torx screw.
- 6** Insert the bolt and function check the trigger.
- 7** The trigger is adjustable for pull weight and overtravel. Your trigger is set for 11lb. To increase the pull weight turn the bottom screw clockwise or counter clockwise to reduce pull weight. To increase over travel turn the top screw counter clockwise or clockwise to reduce overtravel. The trigger can be set from ~10oz to ~2lbs and over travel from zero to infinity.
- 8** You are now ready to enjoy your new Timney Trigger

NOTE: If you are experiencing "slam fire" issues then the pull weight has been set too low. Increase the pull weight a 1/4-turn at a time. If the trigger is locked, the overtravel has been set too short. Reduce the overtravel 1-4-turn at a time.

MADE IN THE
USA



IF YOU HAVE TROUBLE CHECK OUT TROUBLESHOOTING STEPS ON WWW.TIMNEYTRIGGERS.COM OR CONTACT US

Need help with your install? Contact our customer service team via phone or email for assistance.

Phone: 623-223-1111 Fax: 623-223-1112 Support: technicalsupport@timneyusa.com

